



LM-ATV600-1

580cc 4x4 ATV

Powered by a 580CC Single-cylinder 4-stroke liquid-cooled 4 valves engine delivering 34Kw(6500±500r/min) with 2WD/4WD/Front differential lock EPS. Engineered for rugged terrain, this LM-ATV600-1 is built to handle work, adventure and everyday versatility with confidence.

KEY FEATURES

- ✓ 580cc Engine
- ✓ 2WD/4WD + Front Differential Lock
- ✓ Independent Front Suspension
- ✓ 27x9-14 / 27x11-14 Tires
- ✓ Standard Winch 2500 LBS
- ✓ 46 HP Power Output
- ✓ EPS Electric Power Steering
- ✓ Hydraulic Disc Brakes
- ✓ Digital Instrument Panel
- ✓ Agile 4x4 Off-Road Chassis



Engine & Drivetrain

Engine Type	Single-cylinder , 4-stroke liquid-cooled, 4 valves
Displacement	580CC
Bore x Stroke (mm/in)	89.1*89.2
MAX POWER/RPM	34Kw(6500±500r/min)
HORSEPOWER	46HP
MAX TORQUE	51N.m(6000r/min)
Fuel Supply	BOSCH EFI
Transmission	CVT
Max Speed	100 km/h
Starting type	Electric start
Gear shift /order	Manually/ P—R—N—H—L
Drive System	2WD/4WD/Front differential lock EPS
Fuel Capacity(L/gal)	20 / 5.28

Dimensions

Length x Width x Height (mm/in)	2200*1180*1270/86.6*46.5*50
Wheelbase (mm/in)	1370 / 53.9
Seat Height (mm/in)	900/35.4
Front/Rear Track (mm/in)	970 /38.2
Ground Clearance(mm/in)	310mm
Dry Weight (kg/lbs)	390
Gross Weight	460
Passenger Capacity	2
Battery capacity	12V30Ah

Optional Accessories

Standard equipment only

Brakes

Front/Rear Brakes	Four wheel hydraulic discs+ rear wheel parking
-------------------	--

Suspension & Tires

Front /Rear Suspension	Double A-arm independent suspension
Front/Rear Shock Absorber	Coil spring + oil damping
Front Tires	ATV 25 ×8- 12
Rear Tires	ATV 25 ×10- 12
Rim	Front: 12×6.0 Rear: 12×8

Loading Information

Gross Weight	460
--------------	-----

SUZHOU LEXSONG ELECTROMECHANICAL EQUIPMENT CO. LTD.

Room 504, Building 1, Jiarui Mansion, No.400 Suzhou Ave. East, Suzhou Industrial Park, China

Tel: +86 137 7167 0476 | Email: sales@lextrain.com

WhatsApp: +86 180 1370 1098 | Website: www.lextrain.com