



LS-ATV300

300cc ATV

Powered by a 300CC BASHAN Water Cooled OHC Balance Shaft engine delivering 13.5Kw(7000±500r/min) with Chain Drive 530H. Engineered for rugged terrain, this LS-ATV300 is built to handle work, adventure and everyday versatility with confidence.

KEY FEATURES

- ✓ 300cc Engine
- ✓ Independent Front Suspension
- ✓ 25x8-12 / 25x10-12 Tires
- ✓ Electric Start
- ✓ Comfortable Ergonomic Riding
- ✓ 18 HP Power Output
- ✓ Hydraulic Disc Brakes
- ✓ Digital Instrument Panel
- ✓ Balanced Power & Agility
- ✓ All-Terrain Capability



Engine & Drivetrain

Engine Type	BASHAN, Water Cooled, OHC, Balance Shaft
Displacement	300CC
Compression Ratio	10.5:1
MAX POWER/RPM	13.5Kw(7000±500r/min)
HORSEPOWER	18.1HP
MAX TORQUE	20.5N.m(5200±500r/min)
Fuel Supply	Carburator, JKP230
Transmission	CVT, F-N-R
Max Speed	75km/h
Starting type	Electric start
Drive System	Chain Drive 530H
Fuel Capacity(L/gal)	8.5 / 2.25

Dimensions

Length x Width x Height (mm/in)	1950*1090*915/76.8*42.9*36
Wheelbase (mm/in)	770 / 30.3
Front/Rear Track (mm/in)	880 /34.6
Ground Clearance(mm/in)	340/13.4
Dry Weight (kg)	230
Gross Weight (kg)	310
Battery capacity	12V20Ah
Rear cargo box	Optional, USD96.00

Optional Accessories

2500 LBS Winch	Metal Decorative Bumper
Rear Cargo Box	

Brakes

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore front and rear calipers
-------------------	---

Suspension & Tires

Front /Rear Suspension	Front Double A-arm independent suspension/Rear Swing Arm
Front Tires	ATV 25 ×8- 12
Rear Tires	ATV 25 ×10- 12
Rim	Cast Aluminum

SUZHOU LEXSONG ELECTROMECHANICAL EQUIPMENT CO. LTD.

Room 504, Building 1, Jiarui Mansion, No.400 Suzhou Ave. East, Suzhou Industrial Park, China
Tel: +86 137 7167 0476 | Email: sales@lextrain.com
WhatsApp: +86 180 1370 1098 | Website: www.lextrain.com