

Unleash the Wild Command Every Terrain

LEXSONG

Website: www.lextrain.com

Email: sales@lextrain.com

Tel/WhatsApp: +86 180 1370 1098

Add: Room 504, No.1 Building, No.400 Suzhou Ave. East
Industrial Park, Suzhou City, Jiangsu Province, China



LEXTRAIN



ATV UTV SSV

ATV



MUD VERSION



LM-ATV1000

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	2450x1290x1500mm
Wheelbase	1493mm
Seat Height	933mm
Front/Rear Track	1000mm/1000mm
Ground Clearance	330mm
Fuel Capacity (L/Gal)	18.17/4.8
Dry Weight/Payload Capacity	460kg/336kg
ENGINE	
Engine Type	4-Stroke V-Twin, SOHC
Displacement	976cc
Max.POWER/Horsepower	72KW/97HP (@7300RPM)
Max.Torque	95NM (@5500RPM)
Fuel Supply	BOSCH EFI
Transmission	CVT Shaft
Max.Speed	95km/h
CHASSIS	
Drive System	2WD/4WD with Front Differential LOCK and EPS
Front/Rear Suspension	Front double wishbone independent; rear Torsional Trailing Arm
Brake System	Front and rear dual 260mm 2-piston hydraulic disc brake
Wheel/Tire	Aluminum wheel, front 28x9-14 rear 28x11-14 off road tire

COLORS



WHITE



RED



YELLOW



BLACK




BLUE

COLORS




WHITE



RED



YELLOW



BLACK



BLUE

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	2320x1230x1550mm
Wheelbase	1470mm
Seat Height	910mm
Front/Rear Track	990mm/940mm
Ground Clearance	330mm
Fuel Capacity (L/Gal)	25/6.6
Dry Weight/Payload Capacity	430kg/285kg
ENGINE	
Engine Type	Single-cylinder, 4-Stroke liquid-cooled, 4 valves SOHC
Displacement	976cc
Max.POWER/Horsepower	66KW/90HP (@7200RPM)
Max.Torque	95NM (@6000RPM)
Fuel Supply	BOSCH EFI
Transmission	CVT Shaft
Max.Speed	100km/h
CHASSIS	
Drive System	2WD/4WD with Front Differential LOCK and EPS
Front/Rear Suspension	Double wishbone independent, with airbag shock absorber
Brake System	Front and rear hydraulic disc brake
Wheel/Tire	Aluminum rim, front 14x7.0, rear 14x8.5, 29x9-14 off road tire

MUD VERSION



LM-ATV1000-1

Standard VERSION



LS-ATV600

DIMENSIONS & WEIGHT

Overall Dimensions (LxWxH)	2200x1180x1270mm
Wheelbase	1370mm
Seat Height	900mm
Front/Rear Track	970mm/970mm
Ground Clearance	280mm
Fuel Capacity (L/Gal)	20/5.28
Dry Weight/Payload Capacity	390kg/205kg

ENGINE

Engine Type	Single-cylinder, 4-Stroke liquid-cooled, 4 valves SOHC
Displacement	580cc
Max.POWER/Horsepower	34KW/46HP (@6500RPM)
Max.Torque	51NM (@6000RPM)
Fuel Supply	BOSCH EFI
Transmission	CVT Shaft
Max.Speed	90km/h

CHASSIS

Drive System	2WD/4WD with Front Differential LOCK and EPS
Front/Rear Suspension	Double wishbone independent; Coil Spring and oil damping
Brake System	Front and rear hydraulic disc brake
Wheel/Tire	Aluminum wheel, front 25x8-12 rear 25x10-12 off road tire

COLORS



WHITE



RED



YELLOW



BLACK




BLUE

COLORS



WHITE



RED



YELLOW



BLACK



BLUE

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	2130x1230x1270mm
Wheelbase	1300mm
Seat Height	910mm
Front/Rear Track	990mm/940mm
Ground Clearance	245mm
Fuel Capacity (L/Gal)	20/5.28
Dry Weight/Payload Capacity	400kg/205kg
ENGINE	
Engine Type	Single-cylinder, 4-Stroke liquid-cooled, 4 valves SOHC
Displacement	580cc
Max.POWER/Horsepower	34KW/46HP (@6500RPM)
Max.Torque	51NM (@6000RPM)
Fuel Supply	BOSCH EFI
Transmission	CVT Shaft
Max.Speed	100km/h
CHASSIS	
Drive System	2WD/4WD with Front Differential LOCK and EPS
Front/Rear Suspension	Double wishbone independent; Coil Spring and oil damping
Brake System	Front and rear hydraulic disc brake + rear wheel parking brake
Wheel/Tire	Aluminum wheel, front 25x8-12 rear 25x10-12 off road tire

Standard VERSION



LS-ATV600-1



MUD VERSION

LM-ATV600

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	2200x1180x1270mm
Wheelbase	1370mm
Seat Height	900mm
Front/Rear Track	970mm/970mm
Ground Clearance	280mm
Fuel Capacity (L/Gal)	20/5.28
Dry Weight/Payload Capacity	390kg/205kg
ENGINE	
Engine Type	Single-cylinder, 4-Stroke liquid-cooled, 4 valves SOHC
Displacement	580cc
Max.POWER/Horsepower	34KW/46HP (@6500RPM)
Max.Torque	51NM (@6000RPM)
Fuel Supply	BOSCH EFI
Transmission	CVT Shaft
Max.Speed	90km/h
CHASSIS	
Drive System	2WD/4WD with Front Differential LOCK and EPS
Front/Rear Suspension	Double wishbone independent; Coil Spring and oil damping
Brake System	Front and rear hydraulic disc brake
Wheel/Tire	Aluminum wheel, front 25x8-12 rear 25x10-12 off road tire

COLORS



WHITE



RED



YELLOW



BLACK




BLUE

COLORS




WHITE



RED



YELLOW



BLACK



BLUE

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	2330x1240x1495mm
Wheelbase	1470mm
Seat Height	910mm
Front/Rear Track	990mm/940mm
Ground Clearance	290mm
Fuel Capacity (L/Gal)	20/5.28
Dry Weight/Payload Capacity	430kg/285kg
ENGINE	
Engine Type	Single-cylinder, 4-Stroke liquid-cooled, 4 valves SOHC
Displacement	580cc
Max.POWER/Horsepower	34KW/46HP (@6500RPM)
Max.Torque	51NM (@6000RPM)
Fuel Supply	BOSCH EFI
Transmission	CVT Shaft
Max.Speed	100km/h
CHASSIS	
Drive System	2WD/4WD with Front Differential LOCK and EPS
Front/Rear Suspension	Double wishbone independent, with airbag shock absorber
Brake System	Front and rear hydraulic disc brake
Wheel/Tire	Aluminum rim, front 14x7.0, rear 14x8.5, 29x9-14 off road tire

MUD VERSION



LM-ATV600-1



Standard VERSION

LS-ATV500

DIMENSIONS & WEIGHT

Overall Dimensions (LxWxH)	2200x1180x1270mm
Wheelbase	1370mm
Seat Height	900mm
Front/Rear Track	970mm/970mm
Ground Clearance	280mm
Fuel Capacity (L/Gal)	20/5.28
Dry Weight/Payload Capacity	390kg/205kg

ENGINE

Engine Type	Single-cylinder, 4-Stroke liquid-cooled, 4 valves SOHC
Displacement	495cc
Max.POWER/Horsepower	29KW/39.4HP (@6750RPM)
Max.Torque	44NM (@6000RPM)
Fuel Supply	BOSCH EFI
Transmission	CVT Shaft
Max.Speed	85km/h

CHASSIS

Drive System	2WD/4WD with Front Differential LOCK and EPS
Front/Rear Suspension	Double wishbone independent; Coil Spring and oil damping
Brake System	Front and rear hydraulic disc brake
Wheel/Tire	Aluminum wheel, front 25x8-12 rear 25x10-12 off road tire


COLORS



COLORS




WHITE



RED



YELLOW



BLACK



BLUE

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	2130x1230x1270mm
Wheelbase	1300mm
Seat Height	910mm
Front/Rear Track	990mm/940mm
Ground Clearance	245mm
Fuel Capacity (L/Gal)	20/5.28
Dry Weight/Payload Capacity	400kg/205kg
ENGINE	
Engine Type	Single-cylinder, 4-Stroke liquid-cooled, 4 valves SOHC
Displacement	495cc
Max.POWER/Horsepower	29KW/39.4HP (@6500RPM)
Max.Torque	44NM (@6000RPM)
Fuel Supply	BOSCH EFI
Transmission	CVT Shaft
Max.Speed	95km/h
CHASSIS	
Drive System	2WD/4WD with Front Differential LOCK and EPS
Front/Rear Suspension	Double wishbone independent; Coil Spring and oil damping
Brake System	Front and rear hydraulic disc brake + rear wheel parking brake
Wheel/Tire	Aluminum wheel, front 25x8-12 rear 25x10-12 off road tire

Standard VERSION



LS-ATV500-1



LS-ATV300

DIMENSIONS & WEIGHT

Overall Dimensions (LxWxH)	1950x1090x915mm
Wheelbase	770mm
Ground Clearance	340mm
Fuel Capacity (L/Gal)	8.5/2.25
Dry Weight/Payload Capacity	390kg/280kg

ENGINE

Engine Type	BASHAN,Water Cooled, OHC,Balance Shaft
Displacement	300cc
Max.POWER/Horsepower	13.5KW/18.1HP (@7000RPM)
Max.Torque	20.5NM (@6200RPM)
Fuel Supply	Carburator, JKPZ30
Transmission	CVT Shaft
Max.Speed	75km/h

CHASSIS

Drive System	Chain Drive 530H
Front/Rear Suspension	Front double wishbone independent; rear swing arm
Brake System	4-Wheel Hydraulic Disc with Dual- Bore Front and Rear Calipe
Wheel/Tire	Aluminum wheel, front 25x8-12 rear 25x10-12 off road tire

COLORS



WHITE



RED



YELLOW



BLACK



BLUE

COLORS



WHITE



RED



YELLOW



BLACK



BLUE

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	2110x1160x1330mm
Wheelbase	820mm
Seat Height	480mm
Ground Clearance	180mm
Fuel Capacity (L/Gal)	8.5/2.25
Dry Weight/Payload Capacity	245kg/280kg
ENGINE	
Engine Type	Loncin brand 175ml, SOHC, 4 strokes, single sylinder
Displacement	200cc
Max.POWER/Horsepower	9KW/12.07HP (@8000RPM)
Max.Torque	13NM (@6000RPM)
Fuel Supply	Carburator
Transmission	CVT Shaft
Max.Speed	55km/h
CHASSIS	
Drive System	O-ring chain drive
Front/Rear Suspension	Front independent A-arm dual shock, rear single shock
Brake System	Front and rear hydraulic disc brake
Wheel/Tire	Aluminum wheel, front 25x8-12 rear 25x10-12 off road tire



LS-ATV200



UTV/SSV



LB3-UTV1000

DIMENSIONS & WEIGHT

Overall Dimensions (LxWxH)	3175x1950x2285mm
Cargo Box Dimensions (LxWxH)	820x1410x250mm
Wheelbase	2258mm
Front/Rear Track	1670mm/1590mm
Ground Clearance	340mm
Fuel Capacity (L/Gal)	30/7.9
Dry Weight/Payload Capacity	860kg/490kg

ENGINE

Engine Type	4-Stroke V-Twin, SOHC, CFMOTO Engine
Displacement	996.6cc
Max.POWER/Horsepower	60KW/81HP (@6500RPM)
Max.Torque	95NM (@5500RPM)
Fuel Supply	BOSCH EFI
Transmission	CVT Shaft
Max.Speed	90km/h

CHASSIS

Drive System	2WD/4WD with Front Differential LOCK and EPS
Front/Rear Suspension	Front and rear double wishbone independent
Brake System	Front and rear hydraulic disc brake, with dual bore calipers
Wheel/Tire	Aluminum wheel, front 27x9-14 rear 27x11-14 off road tire

COLORS



WHITE



RED



YELLOW



BLACK



BLUE

COLORS



WHITE



RED



YELLOW



BLACK



BLUE

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	3930x1950x2285mm
Cargo Box Dimensions (LxWxH)	820x1480x390
Wheelbase	2990mm
Front/Rear Track	1670mm/1590mm
Ground Clearance	350mm
Fuel Capacity (L/Gal)	30/7.9
Dry Weight/Payload Capacity	968kg/730kg
ENGINE	
Engine Type	4-Stroke V-Twin, SOHC, CFMOTO Engine
Displacement	996.6cc
Max.POWER/Horsepower	60KW/81HP (@6500RPM)
Max.Torque	95NM (@5500RPM)
Fuel Supply	BOSCH EFI
Transmission	CVT Shaft
Max.Speed	90km/h
CHASSIS	
Drive System	2WD/4WD with Front Differential LOCK and EPS
Front/Rear Suspension	Front and rear double wishbone independent
Brake System	Front and rear hydraulic disc brake, with dual bore calipers
Wheel/Tire	Aluminum wheel, front 27x9-14 rear 27x11-14 off road tire



LB6-UTV1000



LW3-UTV1000

DIMENSIONS & WEIGHT

Overall Dimensions (LxWxH)	3270x1950x2115mm
Cargo Box Dimensions (LxWxH)	828x1448x390mm
Wheelbase	2258mm
Front/Rear Track	1670mm/1590mm
Ground Clearance	380mm
Fuel Capacity (L/Gal)	30/7.9
Dry Weight/Payload Capacity	875kg/490kg

ENGINE

Engine Type	4-Stroke V-Twin, SOHC, CFMOTO Engine
Displacement	996.6cc
Max.POWER/Horsepower	60KW/81HP (@6500RPM)
Max.Torque	95NM (@5500RPM)
Fuel Supply	BOSCH EFI
Transmission	CVT Shaft
Max.Speed	90km/h

CHASSIS

Drive System	2WD/4WD with Front Differential LOCK and EPS
Front/Rear Suspension	Front and rear double wishbone independent
Brake System	Front and rear hydraulic disc brake, with dual bore calipers
Wheel/Tire	Aluminum wheel, front 27x9-14 rear 27x11-14 off road tire

COLORS



WHITE



RED



YELLOW



BLACK



BLUE

COLORS



Yellow



Green

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	3985x1950x2115mm
Cargo Box Dimensions (LxWxH)	828x1448x390mm
Wheelbase	2990mm
Front/Rear Track	1670mm/1590mm
Ground Clearance	350mm
Fuel Capacity (L/Gal)	30/7.9
Dry Weight/Payload Capacity	1080kg/730kg
ENGINE	
Engine Type	4-Stroke Single Cylinder, Liquid cooling
Displacement	996.6cc
Max.POWER/Horsepower	60KW/81HP (@6500RPM)
Max.Torque	95NM (@5500RPM)
Fuel Supply	BOSCH EFI
Transmission	CVT Shaft
Max.Speed	90km/h
CHASSIS	
Drive System	2WD/4WD with Front Differential LOCK and EPS
Front/Rear Suspension	Front and rear double wishbone independent
Brake System	Front and rear hydraulic disc brake, with dual bore calipers
Wheel/Tire	Aluminum wheel, front 27x9-14 rear 27x11-14 off road tire



LW6-UTV1000



LW3C-UTV1000

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	3270x1950x2115mm
Cargo Box Dimensions (LxWxH)	828x1448x390mm
Wheelbase	2258mm
Front/Rear Track	1670mm/1590mm
Ground Clearance	380mm
Fuel Capacity (L/Gal)	30/7.9
Dry Weight/Payload Capacity	875kg/490kg
ENGINE	
Engine Type	4-Stroke V-Twin, SOHC, CFMOTO Engine
Displacement	963cc
Max.POWER/Horsepower	60KW/81HP (@6500RPM)
Max.Torque	95NM (@5500RPM)
Fuel Supply	BOSCH EFI
Transmission	CVT Shaft
Max.Speed	90km/h
CHASSIS	
Drive System	2WD/4WD with Front Differential LOCK and EPS
Front/Rear Suspension	Front and rear double wishbone independent
Brake System	Front and rear hydraulic disc brake, with dual bore calipers
Wheel/Tire	Aluminum wheel, front 27x9-14 rear 27x11-14 off road tire

COLORS




WHITE



RED



YELLOW



BLACK



BLUE

COLORS



Yellow



Green

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	3985x1950x2115mm
Cargo Box Dimensions (LxWxH)	828x1448x390mm
Wheelbase	2990mm
Front/Rear Track	1670mm/1590mm
Ground Clearance	350mm
Fuel Capacity (L/Gal)	30/7.9
Dry Weight/Payload Capacity	1080kg/730kg
ENGINE	
Engine Type	4-Stroke Single Cylinder, Liquid cooling
Displacement	996.6cc
Max.POWER/Horsepower	60KW/81HP (@6500RPM)
Max.Torque	95NM (@5500RPM)
Fuel Supply	BOSCH EFI
Transmission	CVT Shaft
Max.Speed	90km/h
CHASSIS	
Drive System	2WD/4WD with Front Differential LOCK and EPS
Front/Rear Suspension	Front and rear double wishbone independent
Brake System	Front and rear hydraulic disc brake, with dual bore calipers
Wheel/Tire	Aluminum wheel, front 27x9-14 rear 27x11-14 off road tire



LW6C-UTV1000



LF-UTV400

DIMENSIONS & WEIGHT

Overall Dimensions (LxWxH)	2700x1450x1750mm
Wheelbase	1980mm
Front/Rear Track	1250mm/1150mm
Ground Clearance	300mm
Fuel Capacity (L/Gal)	9.5/2.1
Dry Weight/Payload Capacity	440kg/260kg

ENGINE

Engine Type	4-Stroke Single Cylinder, Liquid cooling
Displacement	400cc
Max.POWER/Horsepower	18KW/25HP (@6500RPM)
Fuel Supply	EFI/Carburetor
Transmission	CVT Shaft
Max.Speed	75km/h

CHASSIS

Drive System	Rear Wheel Drive
Front/Rear Suspension	Front double wishbone independent; Rear 4-link bar suspension
Brake System	Front and rear 220mm dual hydraulic disc brake
Wheel/Tire	Aluminum wheel, front 25x8-12 rear 25x10-12 off road tire

COLORS



Yellow



Green

COLORS



BLUE



RED



YELLOW



BLACK



PURPE

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	3345x1700x2050mm
Bed Box Dimensions (LxWxH)	720x570x178mm
Wheelbase	2286mm
Front/Rear Track	1443mm/1387mm
Ground Clearance	360mm
Fuel Capacity (L/Gal)	30/7.9
Dry Weight/Payload Capacity	626kg/336kg
ENGINE	
Engine Type	4-Stroke V-Twin, SOHC, CFMOTO Engine
Displacement	976cc
Max.POWER/Horsepower	62.5KW/85HP (@7500RPM)
Max.Torque	87NM (@5500RPM)
Fuel Supply	BOSCH EFI
Transmission	CVT Shaft
Max.Speed	110km/h
CHASSIS	
Drive System	2WD/4WD with Front Differential LOCK and EPS
Front/Rear Suspension	Front double wishbone independent, rear trailing arm
Brake System	Front and rear hydraulic disc brake, with dual bore calipers
Wheel/Tire	Aluminum wheel, front 28x9-14 rear 28x11-14 off road tire



L2-SSV1000



L4-SSV1000

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	3980x1700x2050mm
Bed Box Dimensions (LxWxH)	720x570x178mm
Wheelbase	2986mm
Front/Rear Track	1443mm/1387mm
Ground Clearance	360mm
Fuel Capacity (L/Gal)	30/7.9
Dry Weight/Payload Capacity	790kg/436kg
ENGINE	
Engine Type	4-Stroke V-Twin, SOHC, CFMOTO Engine
Displacement	976cc
Max.POWER/Horsepower	62.5KW/85HP (@7500RPM)
Max.Torque	87NM (@5500RPM)
Fuel Supply	BOSCH EFI
Transmission	CVT Shaft
Max.Speed	110km/h
CHASSIS	
Drive System	2WD/4WD with Front Differential LOCK and EPS
Front/Rear Suspension	Front double wishbone independent, rear trailing arm
Brake System	Front and rear hydraulic disc brake, with dual bore calipers
Wheel/Tire	Aluminum wheel, front 28x9-14 rear 28x11-14 off road tire

COLORS




BLUE



RED



YELLOW



BLACK



PURPE

COLORS



BLUE



RED



YELLOW



BLACK



PURPE

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	2700x1450x1760mm
Wheelbase	1980mm
Front/Rear Track	1250mm/1150mm
Ground Clearance	300mm
Fuel Capacity (L/Gal)	9.5/2.1
Dry Weight/Payload Capacity	380kg/336kg
ENGINE	
Engine Type	4-Stroke, Single-Cylinder, Liquid cooled
Displacement	400cc
Max.POWER/Horsepower	18KW/25HP (@6500RPM)
Max.Torque	25N.M. (@5000RPM)
Fuel Supply	EFI/Carburetor
Transmission	CVT Shaft
Max.Speed	75km/h
CHASSIS	
Drive System	Shaft Drive
Front/Rear Suspension	Front double wishbone independent; Rear 4-link bar suspension
Brake System	Front and rear 220mm dual hydraulic disc brake
Wheel/Tire	Aluminum wheel, front 25x8-12 rear 25x10-12 off road tire



L2-SSV400



L2S-SSV400

DIMENSIONS & WEIGHT

Overall Dimensions (LxWxH)	3250x1520x1750mm
Wheelbase	1980mm
Front/Rear Track	1380mm/1520mm
Ground Clearance	300mm
Fuel Capacity (L/Gal)	9.5/2.1
Dry Weight/Payload Capacity	380kg/336kg

ENGINE

Engine Type	4-Stroke, Single-Cylinder, Liquid cooled
Displacement	400cc
Max.POWER/Horsepower	18KW/25HP (@6500RPM)
Fuel Supply	EFI/Carburetor
Transmission	CVT Shaft
Max.Speed	75km/h

CHASSIS

Drive System	Shaft Drive
Front/Rear Suspension	Front double wishbone independent; Rear 4-link bar suspension
Brake System	Front and rear 220mm dual hydraulic disc brake
Wheel/Tire	Aluminum wheel, front 25x8-12 rear 25x10-12 off road tire

COLORS



COLORS



BLUE



RED



YELLOW



BLACK



PURPE

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	3360x1450x1750mm
Wheelbase	2800mm
Front/Rear Track	1250mm/1150mm
Ground Clearance	300mm
Fuel Capacity (L/Gal)	9.5/2.1
Dry Weight/Payload Capacity	480kg/496kg
ENGINE	
Engine Type	4-Stroke, Single-Cylinder, Liquid cooled
Displacement	400cc
Max.POWER/Horsepower	18KW/25HP (@6500RPM)
Fuel Supply	EFI/Carburetor
Transmission	CVT Shaft
Max.Speed	75km/h
CHASSIS	
Drive System	Shaft Drive
Front/Rear Suspension	Front double wishbone independent; Rear 4-link bar suspension
Brake System	Front and rear 220mm dual hydraulic disc brake
Wheel/Tire	Aluminum wheel, front 25x8-12 rear 25x10-12 off road tire



L4-SSV400



L2-SSV350

DIMENSIONS & WEIGHT

Overall Dimensions (LxWxH)	2645x1515x1710mm
Wheelbase	2025mm
Front/Rear Track	1270mm/1180mm
Ground Clearance	350mm
Fuel Capacity (L/Gal)	16/5
Dry Weight/Payload Capacity	375kg/210kg

ENGINE

Engine Type	4-Stroke, Single-Cylinder, SOHC-4 Valves
Displacement	311cc
Max.POWER/Horsepower	17KW/24HP (@6500RPM)
Max.Torque	25NM (@5000RPM)
Fuel Supply	BOSCH EFI
Transmission	CVT Shaft
Max.Speed	75km/h

CHASSIS

Drive System	Shaft Drive, RWD
Steering System	Rack &Pinion with EPS
Front/Rear Suspension	Front double wishbone independent, rear trailing arm
Brake System	Front and rear hydraulic disc brake, with dual bore calipers
Wheel/Tire	Aluminum wheel, front 25x8-12 rear 25x10-12 off road tire

COLORS



BLUE



RED



YELLOW



BLACK



PURPE

COLORS



BLUE



RED



YELLOW



BLACK



PURPE

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	2450x1270x1670mm
Wheelbase	1885mm
Front/Rear Track	1020mm/1000mm
Ground Clearance	180mm
Fuel Capacity (L/Gal)	9.5/2.1
Dry Weight/Payload Capacity	280kg/210kg
ENGINE	
Engine Type	4-Stroke, Single-Cylinder, OHV, air/oil cooled
Displacement	232cc
Max.POWER/Horsepower	10.5KW/14.5HP (@7500RPM)
Fuel Supply	EFI/Carburetor
Transmission	CVT Shaft
Max.Speed	60km/h
CHASSIS	
Drive System	Shaft Drive, RWD
Front/Rear Suspension	Front double wishbone independent, rear swing arm
Brake System	Front and rear hydraulic disc brake
Wheel/Tire	Aluminum wheel, front 21x7-10 rear 22x10-10 off road tire



L2-SSV250



L2-SSV200A

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	2450x1270x1670mm
Wheelbase	1860mm
Front/Rear Track	1020mm/965mm
Ground Clearance	152mm
Fuel Capacity (L/Gal)	9.5/2.1
Dry Weight/Payload Capacity	290kg/160kg
ENGINE	
Engine Type	4-Stroke, Single-Cylinder, Air/Oil Cooled
Displacement	175cc
Max.POWER/Horsepower	7.6KW/10.5HP (@7000RPM)
Fuel Supply	Carburetor
Transmission	CVT
Max.Speed	55km/h
CHASSIS	
Drive System	Chain Drive
Front/Rear Suspension	Front double wishbone independent, rear swing arm
Brake System	Front and rear hydraulic disc brake
Wheel/Tire	Aluminum wheel, front 21x7-10 rear 22x1-10 off road tire

COLORS

BLUE

RED

YELLOW

BLACK

PURPE

COLORS



BLUE



RED



YELLOW



BLACK



PURPE

DIMENSIONS & WEIGHT	
Overall Dimensions (LxWxH)	2430x1220x1550mm
Bed Box Dimensions (LxWxH)	1600x330x90mm
Wheelbase	1890mm
Front/Rear Track	960mm/940mm
Ground Clearance	175mm
Fuel Capacity (L/Gal)	10/2.64
Dry Weight/Payload Capacity	265kg/210kg
ENGINE	
Engine Type	4-Stroke, Single-Cylinder, OHV, air cooled
Displacement	177.3cc
Max.POWER/Horsepower	7.3KW/9.9HP (@7500RPM)
Max.Torque	10NM (@6000RPM)
Fuel Supply	EFI
Transmission	CVT Shaft
Max.Speed	55km/h
CHASSIS	
Drive System	Shaft Drive, RWD
Front/Rear Suspension	Front double wishbone independent, rear swing arm
Brake System	Front and rear hydraulic disc brake
Wheel/Tire	Aluminum wheel, front 22x7-10 rear 22x10-10 off road tire



L2-SSV200B